

## Exide





Sprinter P/XP  
Design Life 10-12 Jahre

- Hervorragende Hochstromeigenschaften  
Für Gefahrenmeldetechnik, USV, Sicherheitsbeleuchtung




Artikel Nr.	Type	Nenn- spannung V	Nenn- kapazität K10 Ah	Entladung bis 1,8V / K1		Maße mm			An- schluss*	Gewicht kg
				A	L	B	H			
20.05664	P6V1700	6	122,0	92,4	273,0	167,0	191,0	M8	25,00	
20.05666	XP6V2800	6	195,0	138,0	309,0	172,0	241,0	F-M6	32,60	
20.05661	P12V600	12	24,0	17,1	169,0	128,0	175,0	M6	9,50	
20.05660	P12V875	12	41,0	26,6	200,0	169,0	176,0	M6	14,50	
20.05665	XP12V1800	12	56,4	41,6	220,0	172,0	235,0	M6	22,50	
20.05168	P12V1575	12	61,0	43,8	273,0	167,0	191,0	F-M6	24,00	
20.05176	XP12V2500	12	69,5	53,8	262,0	172,0	239,0	F-M6	27,70	
20.05177	XP12V3000	12	92,8	68,9	309,0	172,0	239,0	F-M6	32,80	
20.05178	XP12V3400	12	105,0	77,0	351,0	172,0	239,0	F-M6	36,00	


Anschlussarten:




M-M6



M-M8



F-M8



F-M6