RoHS 2015/863/EU | REACH compliant | Conflict minerals free

GEYER quartz technology

Clock Oscillator SMD-version

+3.3V

part no.	12.73010
model	KXO-V93T
frequency	8.0 MHz
frequency stability at -40° ~ +85°C	±30 ppm
operating temperature	-40° ~ +85°C
storage temperature	-40° ~ +85°C
symmetry	45% ~ 55% at 50% V_{DD} level
rise & fall time max.	5 ns (10% V_{DD} ~ 90% V_{DD} level)/V_{DD}
"O" level max.	VOL: 10% V_{DD}
"1" level min.	VOH: 90% V_{DD}
input voltage V_{DD}	+3.3V DC ±5%
tri-state control voltage (Pin#1)	VIH: V_{DD} x 0.7 min. VIL: V_{DD} x 0.3 max.
input current max.	5 mA
output load max.	15pF (HCMOS)
start up time max.	5 ms
disable delay time max.	200 ns
enable delay time max.	5 ms
stand by current max.	10 µA (Pin #1=VIL)
contents of reel	5000 pcs.

Dimensions (mm):



PIN	CONNECTION	
1	"L"	OPEN or "H"
2	GND	
3	Z	OUTPUT
4	V_{DD}	

Z: high impedance

● :Suggest stand-by terminal

#2 is connected to the metal lid(※1).

Suggested soldering pad:



Reflow soldering condition:



Test circuit:



CL : including fixture and probe capacitance.

Output waveform:



Symmetry=t/T×100(%)

Tape specification:



reel diameter 180 mm

GEYER ELECTRONIC e.K. Lochhamer Schlag 5 82166 Gräfelfing/München
Tel. +49 89 546868-0 quartz@geyer-electronic.de www.geyer-electronic.de